



EFFECTIVE LABORATORY SUPPLIES CC

# Viscometers

## Brookfield Model: DV-I Prime THE ONLY VISCOMETER IN ITS CLASS TO OFFER CONTINUOUS SENSING AND DATA DISPLAY



- Display:
  - Viscosity (cP or mPa•s)
  - % Torque
  - Speed/Spindle
  - Temperature (°C or °F) if optional RTD Temperature Probe installed
- RS-232 PC Interface
- Analog outputs
- 18 speeds
- Direct access to time measurement function (time to torque, time to stop)
- Output connection to printer
- Displays under/over range conditions
- Auto Range Showing
- Scroll keys
- Sleek look with simple-to-use keypad
- Optional RTD Temperature Probe DVP-94Y. If required, the probe must be ordered when the instrument is first purchased.

### Contact

[www.effectivelab.co.za](http://www.effectivelab.co.za) • [info@effectivelab.co.za](mailto:info@effectivelab.co.za) • Telephone: (011) 434-1450/1/2 • Fax: (011) 683-1752



EFFECTIVE LABORATORY SUPPLIES CC

# Viscometers



## Brookfield Model: DV-E OUR LOWEST COST DIGITAL VISCOMETER

- Direct reading of viscosity in cP or mPa•s
- Easy to use:
  - Flip a switch
  - Turn a knob
- Display:
  - Viscosity (cP or mPa•s)
  - % Torque
  - Speed/Spindle
- Spindle speed selection
- Auto range
- 18 speeds

### VISCOSITY RANGE cp(mPa•s)

### SPEEDS

MODEL	Min	Max	RPM	Number of increments
LVDV-E	1 <sup>†</sup>	2M	.3-100	0.475m/s
RVDV-E	100 <sup>††</sup>	13M	.3-100	0.475m/s
HADV-E	200 <sup>††</sup>	26M	.3-100	0.475m/s
HBDV-E	800 <sup>††</sup>	104M	.3-	

<sup>†</sup> 1 cP achieved with UL Adapter accessory. 15 cP on LV with standard spindles

<sup>††</sup> Minimum viscosity is achieved with optional RV/HA/HB-1 spindle.

M = 1 million    cP=Centipoise    mPa•s = Millipascal/seconds

## Contact

[www.effectivelab.co.za](http://www.effectivelab.co.za) • [info@effectivelab.co.za](mailto:info@effectivelab.co.za) • Telephone: (011) 434-1450/1/2 • Fax: (011) 683-1752